

LUKOIL STEELO S

ully synthetic high performance gear lubricant based on poly-alpha-olefins (PAO)

APPROVALS

MEETS REQUIREMENTS

AGMA 250.04
AGMA 9005-D94
DIN 51517-CLP-HC
SEB 181226
US Steel 222,223,224
ISO 12925-1 L-CKT
Provisions of Timken Ltd. for rolling bearings
Failure load level DIN ISO 14635-1 A/8,3/90-M:>12

PRODUCT DESCRIPTION

Oils of the **LUKOIL STEELO S series** shows outstanding aging-stability, best interfacial properties (demulsibility, air release and low foaming), perfect temperature-viscosity-properties combined with perfect shear stability and outstanding cold flow properties.

Perfect cold flow properties allow easy and wearfree start up even at very low temperatures. High viscosity-index and effective anti-wear-additives protect gears also at highest thermal loads. The given viscosity-index of the used base-oil provides absolute shear-stability and long life-time. Oils of the **LUKOIL STEELO S series** provides energy-saving due to low friction for wide temperature-ranges, smooth running of gears also at high temperatures, long oil drain-intervals and long life time of gears.

Oils of the **LUKOIL STEELO S series** can be mixed with mineral gear oils. This eases change from mineral to synthetic oil. Oils of the **LUKOIL STEELO S series** are compatible to commonly used elastomers and lacquers.

APPLICATION

For gears, roller and glider bearings as well as for circulating lubrication systems working at very low and/or very high temperatures.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL STEELO S				
			68	100	220	320	460
density/15°C	kg/m ³	DIN 51757	840	842	846	848	863
flash point COC	°C	ISO 2592	>225	>235	>240	>250	>230
viscosity class	ISO VG		68	100	220	320	460
Viscosity/40°C	mm ² /s	DIN 51562/T1	66	102	216	314	450,7
Viscosity/100°C	mm ² /s	DIN 51562/T1	10,3	14,3	25,2	34,3	46,1
Pourpoint	°C	DIN ISO 3016	<-54	<-48	<-42	<-39	<-36

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

17 May 2016, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy +43(1)205 222-8800
 Ölhafen Lobau – Uferstr. 8
 1220 Vienna - Austria www.lukoil-lubricants.eu

member of:

