

LUKOIL GENESIS ADVANCED 5W-40

Product number: 563041

Semi synthetic multigrade engine oil

APPROVALS

API SN
 MB-Approval 229.3
 VW 502 00/ 505 00

MEETS REQUIREMENTS

ACEA A3/B4, A3/B3
 API CF
 Fiat 9.55535-H2/ M2/ N2
 PSA B71 2296
 Renault RN 0700/ 0710

PRODUCT DESCRIPTION

LUKOIL GENESIS ADVANCED 5W-40 is a semi synthetic multigrade engine oil for today's gasoline and diesel engines without diesel particular filter. It permits severe operating and traffic conditions and thereby guarantees full reliability.

LUKOIL GENESIS ADVANCED 5W-40 winter viscosity reduces friction during cold operation.

LUKOIL GENESIS ADVANCED 5W-40 stable summer viscosity reaches every part of the engine and guarantees highest security during urban stop-and-go-traffic.

LUKOIL GENESIS ADVANCED 5W-40 is qualified for turbo-charged engines and catalytic converters and provide high reserves in performance within the recommended oil drain interval.

LUKOIL GENESIS ADVANCED 5W-40 low volatility reduces oil consumption.

APPLICATION

LUKOIL GENESIS SPECIAL 5W-40 can be used in older car, gasoline and diesel engines without DPF.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS ADVANCED 5W-40
Density/15°C	kg/m ³	DIN 51575	852
Flash point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	5W-40
Viscosity/40°C	mm ² /s	DIN 51562/T1	76
Viscosity/100°C	mm ² /s	DIN 51562/T1	13,1
Viscosity index	---	DIN ISO 2909	175
Pour point	°C	DIN ISO 3016	<-36

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

Oct. 1, 18, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe GmbH
 Uferstrasse 8
 1220 Vienna, Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of::

