

LUKOIL LAYER PROTECT LT

Product number: 580515

Highly effective protection for concrete mixer, applicable on dry and wet surfaces in cold climate areas

APPROVALS

MEETS REQUIREMENTS

PRODUCT DESCRIPTION

LUKOIL LAYER PROTECT LT is characterised by excellent adherence on pumps and drums of concrete mixer including all equipment in contact with fresh concrete. The product secures a chemo-physical separation of concrete and metal surfaces. The curing process of concrete is not affected in any way.

APPLICATION

For a successful and economical use **LUKOIL LAYER PROTECT LT** is best applied with a spray lance after cleaning undiluted evenly and very thin. Regular use of **LUKOIL LAYER PROTECT LT** prevents caking of crusts and ensures effective protection against corrosion.

LUKOIL LAYER PROTECT LT significantly reduces cleaning time and cleaning costs and extend the life of the treated units.

LUKOIL LAYER PROTECT LT is tailor made for very cold climate areas (LT= low temperatures) and is easy to spray even at low temperatures.

consumption:

On cleaned metal surfaces
1 liter for 15 m²

TYPICAL TEST DATA

Property	Unit	Test method	LUKOIL LAYER PROTECT LT
Density at 15°C	kg/m ³	DIN 51757	849
Flash point COC	°C	ISO 2592	>105
Viscosity at 40°C	mm ² /s	DIN 51562/T1	5,2
Pour point	°C	DIN ISO 3016	<-60

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH