

LUKOIL ATF SYNTH

Product number: 583321

fully synthetic, high-performance red colored Transmission Fluid - ATF

APPROVALS

MAN 339 Typ L1/ V2/ Z2
MB-Approval 236.8
RBAS Lubricant Class TE-ML 09X
VOITH H55.6336.xx
ZF TE-ML 04D, 14B, 16L (ZF001782)

MEETS REQUIREMENTS

Allison C-4
Ford MERCON
GM DEXRON II-E
NATO Code H-548
VOLVO 97335
ZF TE-ML 11A, 21L

PRODUCT DESCRIPTION

LUKOIL ATF SYNTH is a fully synthetic, high-performance red colored Automatic Transmission Fluid - ATF. The extremely good viscosity-temperature behaviour ensures maximum gear change precision over broad temperature ranges.

The characteristics of **LUKOIL ATF SYNTH** are applicable in a wide temperature range, highest sheer stability, extremely high oxidation stability, effective corrosion protection, lowest possible foaming characteristics, excellent viscosity-temperature behaviour and the extremely low pour point allows easy gear-shifting also at very low temperatures.

APPLICATION

LUKOIL ATF SYNTH is used as a power transmission fluid in automatic gear boxes of passenger cars, busses, torque-converters, power steering, hydraulic clutches, hydraulic systems (deterging multigrade hydraulic oil ISO VG 32) and as gear oil referring to manufacturer's manuals.

LUKOIL ATF SYNTH can be used in all automatic gear boxes demanding DEXRON® and MERCON® oils.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL ATF SYNTH
Density at 15 °C	kg/m ³	DIN 51575	840
Flash Point COC	°C	ISO 2592	206
Viscosity class	---	ISO VG	32
		SAE J 306	75W-80
Viscosity at 40°C	mm ² /s	DIN 51562/T1	34
Viscosity at 100°C	mm ² /s	DIN 51562/T1	7.2
Viscosity index	---	DIN ISO 2909	183
Pourpoint	°C	DIN ISO 3016	<-48

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Aug. 27, 18, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe GmbH +43(1)205 222-8800
 Uferstrasse 8
 1220 Vienna, Austria www.lukoil-lubricants.eu

member of::

